


 ISO:9001:2015, IATF:16949:2016 ISO:14001:2015, ISO:45001:2018, ISO:50001:2011, RoHS2 Compliant, Sedex/Smeta, G.C. Mark, Trusted Product, TUV For Fire Survival Cable	Price List w.e.f. 20 th May 2026				
	BONTON CABLES (INDIA) PVT. LTD.				
	Plant-1 : A 115 RIICO Industrial Area, Phase-1, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)				
	Plant-2 : A 6A, Kaharani Industrial Area, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)				
E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001					
Bonton Single Core Copper Conductor PVC Cables (Unsheathed)-HRFR					
1100V Grade Conforming to IS:694					
Nominal Area of Conductor sq.mm	HRFR PVC		Std. Pkg. of Coil in Master Carton	HRFR PVC In Project Packing	
	PartNo.	MRP (90 Mtr. Box)		PartNo.	MRP (180 Mtr. Coil)
0.75	110266N	2335	20	110266P	5740
1	110267N	2985	20	110267P	6905
1.5	110268N	4415	16	110268P	10115
2.5	110269N	7205	12	110269P	16525
4	110270N	10665	8	110270P	25280
6	110271N	16120	4	110271P	37780
Standard Packing : 90mtr. In Carton* Project Packing: 180 mtrs. Polywrapped					
Colour Available : Red, Yellow, Blue, Black, White, Green & Grey					
Bonton Single Core Copper Conductor PVC Insulated Cables (Unsheathed) - FRLS(H)					
1100V Grade Conforming to IS:694					
Nominal Area of Conductor sq.mm	FRLS(H) PVC		Std. Pkg. of Coil in Master Carton	FRLS(H) PVC in Project Packing	
	Part No.	MRP (90 Mtr. Box)		Part No.	MRP (180 Mtr. Coil)
0.75	110266NLS	2450	20	110266PLS	6030
1	110267NLS	3135	20	110267PLS	7250
1.5	110268NLS	4635	16	110268PLS	10620
2.5	110269NLS	7565	12	110269PLS	17350
4	110270NLS	11195	4	110270PLS	26545
6	110271NLS	16925	4	110271PLS	39670
Standard Packing : 90mtr. In Carton * Project Packing : 180 mtrs. Polywrapped					
Colour Available : Red, Yellow, Blue, Black, White, Green & Grey					
Bonton Single Core Copper Conductor ZHFR Insulated Cables - ZHFR					
1100V Grade Conforming to IS:17048 (Unsheathed)					
Nominal Area of Conductor sq.mm	ZHFR		Std. Pkg. of Coil in Master Carton	ZHFR in Project Packing	
	Part No.	MRP (90 Mtr. Box)		Part No.	MRP (180 Mtr. Coil)
0.75	110267NZ	3015	20	110267PZ	6430
1	110267NZ	3920	20	110267PZ	7705
1.5	110268NZ	5745	16	110268PZ	11350
2.5	110269NZ	9405	12	110269PZ	18520
4	110270NZ	13835	4	110270PZ	28300
6	110271NZ	20960	4	110271PZ	42295
Standard Packing for ZHFR : 90mtr. In Carton * Project Packing : 180 mtrs. Polywrapped					
Colour Available : Red, Yellow, Blue, Black & Green					
Bonton Single Core Copper Conductor PVC Cables (Unsheathed) - HRFR					
1100V Grade Conforming to IS:694					
Nominal Area of Conductor sq.mm	HRFR PVC		Nominal area of Conductor sq.mm	HRFR PVC	
	Part No.	MRP (100 mtr.)		Part No.	MRP (100 mtr.)
10	110272H	36540	120	110279H	437585
16	110273H	58515	150	110280H	547730
25	110274H	93020	185	110281H	681505
35	110275H	130205	240	110282H	889605
50	110276H	187510	300	110283H	1091765
70	110277H	257355	400	110284H	1454690
95	110278H	349360	500	110285H	1819825
Standard Packing : 100 mtrs. Coils					
Colour available : Red, Yellow, Blue, Black & Green					
* FRLS(H) insulation: 5% Extra					
* HFLS (Halogen Free Insulation) : 12% Extra					



BONTON CABLES (INDIA) PVT. LTD.

E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001

Bonton Single Core Copper Conductor PVC Cables (Unsheathed) - HRFR & FRLSH

1100V Grade Conforming to IS : 694

Nominal Area of Conductor sq.mm	HRFR PVC in Project Packing		FRLSH PVC in Project Packing	
	Part No.	MRP (200 mtr. Coil)	Part No.	MRP (200 Mtr. Coil)
0.5	110265 T	4495	110265 TLS	4720
0.75	110266 T	5860	110266 TLS	6155
1	110267 T	7720	110267 TLS	8105
1.5	110268 T	11320	110268 TLS	11885
2.5	110269 T	18670	110269 TLS	19605
4	110270 T	28320	110270 TLS	29735
6	110271 T	42330	110271 TLS	44445

Colour available : Red, Yellow, Blue, Black, White, Green & Grey

Bonton Jelly Flooded Aluminium Foil & Aluminium Wire Braided Co-Axial Cables

Size	Part No.	100 Meter Unarmoured	305 Meter Unarmoured	1000 Meter Armoured
RG 59	110086	5275	15820	
RG 6	110087	6630	19890	188790
RG 11	110088	14410	43620	288405

Bonton PVC insulated Telephone Cables for Indoor application conforming to TEC Specification G/WIR06/02

No. of Pair (0.40mm)	Part No.	MRP - 100 Mtr. (0.40 mm)	No. of Pair (0.50 mm)	Part No.	MRP - 100 Mtr. (0.50 mm)	No. of Pair (0.61 mm)	Part No.	MRP - 100 Mtr. (0.61 mm)
1	110082	1805	1	110091	2395	1	110101	3645
2	110083	3140	2	110092	3985	2	110102	6940
3	110084	4055	3	110093	6010	3	110103	10365
4	110085	5220	4	110094	7935	4	110104	13980
5	110086	6750	5	110095	9445	5	110105	17360
10	110087	13650	10	110096	19285	10	110106	35985
20	110088	27270	20	110097	38375	20	110107	70375
50	110089	-	50	110098	96885	50	110108	171855
100	110090	-	100	110099	203775	100	110109	343820

Bonton Multi Core Copper Conductor PVC Cables (Sheathed) - FR

1100V Grade Conforming to IS : 694

Nominal Area of Conductor sq.mm	Part No.	2 Core	Part No.	3 Core	Part No.	4 Core	Part No.	5 Core
0.5	110308 2C	5415	110308 3C	7415	110308 4C	9480	110308 5C	11895
0.75	110309 2C	7215	110309 3C	10015	110309 4C	12900	110309 5C	16870
1	110310 2C	9170	110310 3C	12770	110310 4C	16500	110310 5C	21845
1.5	110311 2C	12505	110311 3C	17925	110311 4C	23235	110311 5C	29620
2.5	110312 2C	20565	110312 3C	28960	110312 4C	38355	110312 5C	48655
4	110313 2C	30260	110313 3C	45860	110313 4C	58005	110313 5C	76575
6	110314 2C	44620	110314 3C	67475	110314 4C	85330	110314 5C	112780
10	110315 2C	76125	110315 3C	111995	110315 4C	148040	110315 5C	194505
16	110316 2C	120430	110316 3C	175945	110316 4C	232435	110316 5C	298405
25	110317 2C	200600	110317 3C	292005	110317 4C	381390	110317 5C	542535
35	110318 2C	279365	110318 3C	405725	110318 4C	533170	110318 5C	743280
50	110319 2C	396535	110319 3C	577950	110319 4C	763105	110319 5C	1075705
70	110320 2C	563430	110320 3C	801655	110320 4C	1059630	110320 5C	1470830

Standard Packing : 100 mtrs. Coil

* FRLS(H) insulation : 5% Extra

* HFLS (Halogen Free Insulation) : 12% Extra

 ISO:9001:2015, IATF:16949:2016 ISO:14001:2015, ISO:45001:2018, ISO:50001:2011, RoHS2 Compliant, Sedex/Smeta, G.C. Mark, Trusted Product, TUV For Fire Survival Cable	Price List w.e.f. 20 th May 2026				
	BONTON CABLES (INDIA) PVT. LTD.				
	Plant-1 : A 115 RIICO Industrial Area, Phase-1, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)				
	Plant-2 : A 6A, Kaharani Industrial Area, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)				
E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001					
Bonton PVC Insulated and Sheathed 3 Core Flat Submersible Cable					
1100V grade conforming to IS : 694/1990					
Nominal area of Conductor sq.mm	Part Number				MRP - Per 100 Mtrs.
1.5	110311 3C FT				19970
2.5	110312 3C FT				33210
4	110313 3C FT				47580
6	110314 3C FT				69140
10	110315 3C FT				116685
16	110316 3C FT				180655
25	110317 3C FT				290880
35	110318 3C FT				404865
Bonton PVC Insulated and sheathed 4 Pair Twisted LAN Cable					
Size			MRP 305 Meter		
CAT 6			24795		
Flexible Bare Copper Conductor PVC Insulated Overall Aluminium Mylar Tape Shielded along with ATC Drain wire PVC Outer Sheath Aluminium Myler Tape Wires / Cables (100 Mtr Coil)					
Core	0.5 sq.mm	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq mm
2	8960	11475	13755	17920	28030
3	11095	15100	18220	24245	38760
4	13755	18215	23335	32740	48965
5	16965	22715	27645	37845	61930
6	19610	25770	32260	45555	74130
7	21310	30255	37530	51265	87725
8	24240	32735	41695	57290	97900
10	28725	40450	51265	70875	119685
12	33990	47410	60535	84015	146880
14	39530	55430	69935	96680	
16	44785	62230	78755	111485	
19	51270	74120	93120	129735	
24	63620	90970	115205	165710	
Note : 3% Extra Charges for Drum packing					
FIRE SURVIVAL CABLE					
Bonton Multicore High Proformance Silicon Rubber (HPSR) Insulated LSZH Sheathed Fire Survival Cable - TUV Certified Cable					
Test as per BS:6387 C.W.Z.					
Size	Part No.	MRP - Per Mtr (Un-armoured)		MRP - Per Mtr (Armoured)	
2 Core x 1.5 sq.mm	110331	505		590	
3 Core x 1.5 sq.mm	110332	630		710	
2 Core x 2.5 sq.mm	110333	695		740	
3 Core x 2.5 sq.mm	110334	825		915	
Bonton MICA Tape Multicore XLPE Insulated LSZH sheathed Copper Armoured Fire Survival Cable - TUV Certified Cable					
Test as per BS6387 C.W.Z.					
Size	Part No.	MRP- Per Mtr.			
2 Core x 1.5 sq.mm	110341	455			
3 Core x 1.5 sq.mm	110342	555			
2 Core x 2.5 sq.mm	110343	630			
3 Core x 2.5 sq.mm	110344	780			
Terms & Conditions :-					
1. GST @ 18% Extra on Copper Flexible PVC Insulated Wire & PVC Insulated/Sheathed Cable (HSN Code 85446020)					
2. Order are accepted subject to availability of stocks.					
3. Conductor Resistance as per IS 694 is the governing criteria.					